

DATA SHEET

VIDI 150

4K CONFERENCING CAMERA



The Vidi 150 is a 4K camera for use with conferencing systems. Intended for huddle rooms or small conference rooms, the Vidi 150 has a 120° wide field-of-view, allowing everyone in the room to be seen. It can be table-mounted or attached to the room's display. The Vidi 150 is also equipped with a microphone array and built-in noise cancelling algorithms to ensure everyone in the room is heard clearly, regardless of where they are sitting or standing.

FEATURES

- 4K video quality
- Electronic Pan/Tilt/Zoom with included remote
- Auto framing technology to keep participants in frame, enabled using remote
- Wide 120° field-of-view with no distortion
- Built-in microphone array with two omni-directional microphones
- On-board signal processing for noise cancellation
- Supports wide dynamic range and low light conditions
- USB powered
- Covered by Biamp Systems' three-year warranty

ARCHITECTS & ENGINEERS SPECIFICATIONS

The conferencing camera shall be designed to connect with conferencing systems. The conferencing camera shall be equipped with one USB 3.0 type B port. The conferencing camera shall be able to transmit audio streams over USB via a USB Class 1 Audio device. The conferencing camera shall be capable of transmitting video signals over USB of up to 3840 x 2160 resolution at 30 frames per second. The conferencing camera shall be equipped with a camera having a 120° field-of-view. The conferencing camera shall be equipped with two omni-directional microphones and integrated signal processing for noise cancellation. The conferencing camera shall be CE marked and compliant with the RoHS directive. Warranty shall be three years. The conferencing camera shall be the Vidi 150.

VIDI 150 SPECIFICATIONS

Camera:		USB:	
Image sensor:	8MP, 1/2.5", CMOS, progressive scan	Connector:	USB 3.0 Type-B
Lens:		Bit Depth:	24-bit
Field-Of-View:	120°	Sample Rate:	48 kHz
Focus:	2.8mm	Overall Dimensions:	
Zoom:	3x Digital	Height:	1.7 inches (42 mm)
White Balance:	Auto	Width:	7.6 inches (194 mm)
Backlight Compensation:	Supported	Depth:	1.3 inches (34 mm)
Digital Noise Reduction:	2D and 3D	Weight:	0.7 lbs (340 g)
Signal Noise Ratio:	> 55dB	Ambient Operating Temperature Range:	50-86° F (10-30° C)
Positioning:	Autoframing capability Electronic Pan/Tilt/Zoom	Compliance:	CE Marked (Europe) RoHS Directive (Europe)
Video:			
Supported Resolutions:	Up to 3840 x 2160p (30fps)		
Connector:	USB		

Biamp and Vidi are either trademarks or registered trademarks of Biamp Systems, LLC in the United States and other countries. Other product names referenced may be trademarks or registered marks of their respective owners and Biamp Systems is not affiliated with or sponsored by these companies.